

4C Series

Square Model



Specialized in Custom Design

- Solid steel and aluminum structure**
- High load capacity to withstand severe weather conditions**
- Flat roof with customized pitch**
- Maximum clearance between posts**

Standard colours



6061-T6 aluminum frame (3/16-inch-thick)
 Certified baked paint quality AAMA 2603, AAMA 2604 (on request)
 Grade A2-70 stainless steel or Grade A325 hot-dip galvanized steel
 hardware according to ASTM A153 or ASTM F2329
 Mechanical anchors (optional chemical anchors)
 28-gauge or thicker corrugated steel roof as standard
 44W steel arch
 Option of post and purlin made of grade 50W steel tubes

Available roofs			Dimensions												
Polycarbonate	Corrugated sheet metal	Wood and sheet metal	ww	h	H	S	W	dd	D	Front posts	Back posts	C1	C2	C3	C4
-	x	x	Max 192	Std 80	3:12	-	Max 384	-	-	Std 4 x 4 x 3/16	-	8	-	-	-



Corrugated sheet metal



Corrugated sheet metal



Wood and sheet metal



Wood and sheet metal



Aluminum and glass wall



Privacy panel



Sheet metal



Glass

Wall Options

Glass

6 mm on clips for maximum ventilation

Panels with watertight frame

Several frame finishing options: sheet metal, sheet metal and wood, glass, solid or perforated aluminum panels, etc.

Privacy panels

Choice of 17 standard models or made-to-measure

Combination of options

E.g., Aluminum and glass wall

Also available are our doors, windows, sliding doors and 3-season fixed panels. Doors have the same finishing options as walls.